



H03VV-F

Installation Cable 300/300 V with Cu conductors, PVC insulated, PVC Sheathed Cables

APPLICATION

For household appliances, under medium mechanical stresses, also in damp and wet locations.

CONSTRUCTION

Conductors	: Class5 acc.to IEC 60228
Insulation	: PVC compound
Bedding	: -
Armour	: -
Sheath	: PVC Sheathed

TECHNICAL CHARACTERISTICS

CPR Class	: Eca
Rated Voltage	: 300/300V
Bending Radius	: 6D
Max.conductor Temperature	: 70°C
Max.short-circuit Temperature	: 160°C

CORE IDENTIFICATION

According to HD 308 S2

Insulation Color	:
2 core	: Brown-Blue
3 core	: Green/Yellow-Brown-Blue
4 core	: Blue-Brown-Black-Grey
5 core	: Green/Yellow-Blue-Brown-Black-Grey

Sheath Color	:
White	
Other colours available	

STANDARD

EN 50525-2-11



Trade Mark of MXN KABLO SANAYİ ve TİCARET LTD.ŞTİ.

H03VV-F

Installation Cable 300/300 V with Cu conductors, PVC insulated, PVC Sheathed Cables

Nominal Cross-Section mm ²	Max Resistance at 20°C Ω/km	Outer Dia (Approx.) mm	Cable Weight (Approx.) kg/km	Current Capacity In Earth A	Current Capacity In Air A
2x0,50	39	5,00	36	-	3
2x0,75	26	5,40	44	-	6
3x0,50	39	5,30	43	-	3
3x0,75	26	5,70	54	-	6
4x0,50	39	5,80	51	-	3
4x0,75	26	6,30	65	-	6
5x0,50	39	6,30	64	-	3
5x0,75	26	6,90	81	-	6